# APPENDIX 10-C. VENTING SCENARIOS FOR GAS-FIRED STORAGE WATER HEATERS AT EFFICIENCY LEVEL 2

## TABLE OF CONTENTS

10-C.1 IN	TRODUCTION 10-C-1
10-C.2 LC	CC RESULTS 10-C-1
10-C.3 NI	IA RESULTS 10-C-2
	LIST OF TABLES
Table 10-C.2.	Gas-Fired Storage Water Heaters: LCC and PBP Results (No stainless steel vent connectors required)
Table 10-C.2.	<u>.</u> '
	Results (No stainless steel vent connectors required)
Table 10-C.2.	<b>C</b>
T 11 10 G 2	stainless steel vent connectors required for EL 2)
Table 10-C.2.	$\epsilon$
Table 10-C.3.	Results (100 percent stainless steel vent connectors required for EL 2). 10-C-2  Cumulative National Energy Savings and Consumer Net Present Value for Gas-Fired Storage Water Heaters (No stainless steel vent
Table 10-C.3.	connectors required)
	LIST OF FIGURES
Figure 10-C.3	3.2 NES in Gas-Fired Storage Water Heater Comparison of Scenario Results
Figure 10-C.3	

## APPENDIX 10-C. ANALYSIS RESULTS USING ALTERNATIVE VENTING SCENARIOS FOR GAS-FIRED STORAGE WATER HEATERS AT EFFICIENCY LEVEL 2

### 10-C.1 INTRODUCTION

This appendix presents results for two scenarios associated with the venting options for gas storage water heaters at Efficiency Level 2 (0.63 EF at 40 gallon). As discussed in chapter 8, DOE assumed that all natural-draft gas storage water heater installations of units with RE of 78 percent or higher include stainless steel vent connectors. However, there is uncertainty regarding the fraction of water heater installations that would require a stainless steel vent connector. To develop a range that bounds the cost associated with stainless steel vents, DOE analyzed two scenarios:

- 1. No stainless steel vent connectors required;
- 2. 100% stainless steel vent connectors required for Efficiency Level (EL) 2.

#### 10-C.2 LCC RESULTS

Table 10-C.2.1 Gas-Fired Storage Water Heaters: LCC and PBP Results (No stainless steel vent connectors required)

Efficiency Level ID	Enongy	Life-Cycle Cost (2009\$) Life-Cycle Cost Savings				Payback Period (years)					
	Energy Factor	Average	Average		Average	Households with					
		Installed Price		0	Average	Average	rating LCC	Savings (2009\$)	Net Cost	No Impact	Net Benefit
Baseline	0.59	\$1,032	\$2,473	\$3,505							
1	0.62	\$1,066	\$2,357	\$3,423	\$52	8%	36%	56%	1.6	4.3	
2	0.63	\$1,141	\$2,293	\$3,434	\$42	16%	22%	62%	2.9	12.4	
3	0.64	\$1,559	\$2,286	\$3,845	-\$322	74%	12%	14%	39.8	65.8	
4	0.65	\$1,591	\$2,220	\$3,812	-\$290	73%	6%	21%	29.8	44.2	
5	0.67	\$1,656	\$2,137	\$3,793	-\$273	73%	6%	21%	24.2	30.1	
6	0.77	\$1,893	\$1,878	\$3,771	-\$251	73%	1%	26%	17.1	18.0	

Table 10-C.2.2 Gas-Fired Storage Water Heaters (TSL 5 and 6): LCC and PBP Results (No stainless steel vent connectors required)

Efficiency Level ID Combination	Life-C	Cycle Cost (2	2009\$)	Li	fe-Cycle Cost Savings  Payback Period (years)				
	Average	Average		Average	Households with				
	Installed	Litetime	Average LCC	Savings (2009\$)	Net Cost	No Impact	Net Benefit	Median	Average
1 (small WH) + 6 (large WH)	\$1,098	\$2,330	\$3,427	\$51	10%	33%	57%	1.9	4.6
2 (small WH) + 6 (large WH)	\$1,170	\$2,267	\$3,437	\$42	17%	21%	62%	3.2	12.4

Table 10-C.2.3 Gas-Fired Storage Water Heaters: LCC and PBP Results (100 percent stainless steel vent connectors required for EL 2)

	Enongy	Life-C	Cycle Cost (2	2009\$)	Life-Cycle Cost Savings				k Period ars)					
Efficiency	Energy Factor	Average	Average		Average	Households with								
Level ID		Installed Cherating Average   Saving	Operating	Average	Average	Average	erating   Average   CC	erating   Average   Security   CC   Security	Savings (2009\$)	Net Cost	No Impact	Net Benefit	Median	Average
Baseline	0.59	\$1,079	\$2,473	\$3,552										
1	0.62	\$1,179	\$2,357	\$3,536	\$11	26%	36%	38%	2.0	17.9				
2	0.63	\$1,320	\$2,293	\$3,613	-\$51	47%	22%	30%	14.2	22.8				
3	0.64	\$1,559	\$2,286	\$3,845	-\$258	72%	12%	16%	35.3	55.4				
4	0.65	\$1,591	\$2,220	\$3,812	-\$226	70%	6%	23%	25.7	37.5				
5	0.67	\$1,656	\$2,137	\$3,793	-\$209	70%	6%	24%	21.2	25.9				
6	0.77	\$1,893	\$1,878	\$3,771	-\$187	70%	1%	29%	15.4	16.5				

Table 10-C.2.4 Gas-Fired Storage Water Heaters (TSL 5 and 6): LCC and PBP Results (100 percent stainless steel vent connectors required for EL 2)

	(100 per	cent stain	Tebb beec	1 , 6116 60	micetors	require	d Ioi 13	<i>,</i>	
Efficiency Level ID Combination	Life-C	Cycle Cost (2	2009\$)	Li	Life-Cycle Cost Savings  Payback 1 (year.				
	Average	Average		Average	Hou	Households with			
	Installed Price	nstalled   Lifetime   Ave	Average   Savi	Savings (2009\$)	Net Cost	No Impact	Net Benefit	Median	Average
1 (small WH) + 6 (large WH)	\$1,206	\$2,330	\$3,535	\$14	28%	33%	39%	2.3	17.7
2 (small WH) + 6 (large WH)	\$1,342	\$2,267	\$3,609	-\$47	48%	21%	31%	14.2	22.3

### 10-C.3 NIA RESULTS

Table 10-C.3.1 Cumulative National Energy Savings and Consumer Net Present Value for Gas-Fired Storage Water Heaters (No stainless steel vent connectors required)

Trial			NPV (billio	on 2009\$)
Standard	Efficiency	NES	7%	3%
Level	Level (EF)	(Quads)	Discount	Discount
(TSL)			Rate	Rate
1	0.62	0.69	2.20	5.73
2	0.63	1.17	1.78	6.03
3	0.63	1.17	1.78	6.03
4	0.63	1.17	1.78	6.03
5	0.62	0.79	1.69	4.95
6	0.63	1.27	1.27	5.27
7	0.63	1.17	1.78	6.03
8	0.77	4.91	-12.34	-11.90

Table 10-C.3.2 Cumulative National Energy Savings and Consumer Net Present Value for Gas-Fired Storage Water Heaters (100 percent stainless steel vent connectors required for EL 2)

Trial		_	NPV (billi	on 2009\$)
Standard	Efficiency	NES	7%	3%
Level	Level (EF)	(Quads)	Discount	Discount
(TSL)			Rate	Rate
1	0.62	0.69	0.39	2.35
2	0.63	1.17	-2.28	-1.51
3	0.63	1.17	-2.28	-1.51
4	0.63	1.17	-2.28	-1.51
5	0.62	0.81	0.08	2.02
6	0.63	1.32	-2.39	-1.38
7	0.63	1.17	-2.28	-1.51
8	0.77	4.91	-9.58	-6.77




Figure 10-C.3.2 NES in Gas-Fired Storage Water Heater Comparison of Scenario Results




Figure 10-C.3.3 NPV in Gas-Fired Storage Water Heater Comparison of Scenario Results